



THAI PETROLEUM & TRADING CO.,LTD.

9-10th Floor, TP & T Tower 1, Soi Vibhavadee-Rangsit 19 Chatuchak, Chatuchak, Bangkok 10900, Thailand Tel. (662) 936-1840-48 Fax. (662) 936-1861 http://www.thaipet.com Email:sales@thaiper.com

STATES DIESEL TURBO SILVER

Premium Motor Oil For Heavy-Duty Diesel and Gasoline Engines

Product Descriptions

STATES DEISEL TURBO SILVER provides premium quality service in both diesel and gasoline engines. It is specially formulated for heavy-duty service in diesel engines in both on- and off-highway vehicles as well as heavy-duty construction equipment.

Newly designed low emission diesel engines actually tend to produce more soot; however, this soot is captured in the engine oil and does not go out the exhaust. **STATES DEISEL TURBO SILVER** contains the latest development in dispersant technology to resist oil thickening caused by this soot. The dispersants minimize sludge formation and effectively keep particles in suspension to extend filter life.

STATES DEISEL TURBO SILVER helps control formation of combustion chamber deposits, piston deposits, and varnish that could lead to ring sticking and breakage. It neutralizes acids which commonly found in diesel engines, keeping corrosion wear to a minimum. STATES DEISEL TURBO SILVER provides protection from rust and corrosion, and reduces low-temperature deposits that are common problems in gasoline engines. By providing excellent protection for engine components, it helps extend engine life.

Applications

STATES DEISEL TURBO SILVER is truly universals oil. It is recommended for use in overthe-road diesel trucks, heavy-duty construction equipment, mining equipment, oil field engines, farm vehicles and passenger cars. Because it is also recommended for gasoline engines, STATES DEISEL TURBO SILVER provides mixed-fleet operators the convenience of a single line of motor oils for all vehicles.

Features

- Helps extend engine life
- Recommended for both gasoline and diesel engines
- Recommended for turbocharged diesel engines
- Minimizes piston and combustion chamber deposits
- Fights sludge and vernish
- Effectively neutralizes acids to help keep corrosive wear to a minimum
- Exceeds API CF-4/SG
- Meets or exceeds API CF-4 and CE/SG

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES STATES DIESEL TURBO SILVER

API Service SAE J183 CF-4/SG C Pour Point, °C ASTM D-97 <-27 Flash Point, °C ASTM D-92 238 Viscosity @ 40 °C, cSt ASTM D-445 97.63	Test	AL RESULTS
Viscosity @ 40 °C, cSt	rvice oint, °C	20W-50 CF-4/SG -30
@ 40 °C, cSt ASTM D-445 97.63	,	253
(W, 100 °C, CSt ASTM D-445 13.09		172.6 19.28
Viscosity Index ASTM D-2270 141 Total Base Number , mg kOH/g ASTM D-2896 6.84	ŭ	127 8.16

Rev. 04 Effective Date : October 1, 2020

บริษัท น้ำมันปิโตรเลียมไทย จำกัด

