



THAI PETROLEUM & TRADING CO.,LTD.

9-10th Floor, TP & T Tower 1, Soi Vibhavadee-Rangsit 19
Chatuchak, Chatuchak, Bangkok 10900, Thailand
Tel. (662) 936-1840-48 Fax. (662) 936-1861
<http://www.thaipet.com> Email : sales@thaiper.com

STATES SUPER 2T

Product Descriptions

STATES SUPER 2T is specifically formulated with a unique combination of detergents and ash-free dispersants for higher temperature two-cycle, air-cooled engines. It may be used in any applications, which requires API Service TC lubricants. It is pre-diluted to allow easy mixing with gasoline and smooth flowing in oil injection systems. Because of its special formulation, STATES SUPER 2T is generally not compatible with NMMA TC-W TM, TC-WII TM or TC-W3 TM lubricants. Caution should be exercised to assure that these products are not commingled.

Features

- High temperature protection
- Protects against deposits and ring sticking
- Ideal for air cooled two-cycle engines
- For premix or injection systems
- Prediluted for easier gasoline mixing
- Meet JASO FD, ISO-L- EGD, API TC and มอก. 1040 - 2541

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

STATES SUPER 2T

Test	METHOD	TYPICAL RESULTS
Density @ 30 °C	ASTM D-4052	0.8528
Flash Point (COC) °C	ASTM D-92	96
Pour Point °C	ASTM D-97	-15
Viscosity		
@ 40°C cSt	ASTM D-445	34.44
@ 100°C cSt	ASTM D-445	6.443
Viscosity Index	ASTM D-2270	142
Color	ASTM D-1500	Green
Sulfate Ash, %wt	ASTM D-874	0.10

บริษัท น้ำมันปิโตรเลียมไทย จำกัด

เลขที่ 1 อาคาร ที พี แอนด์ ที ชั้น 9-10 ซอยวิภาวดีรังสิต 19 แขวงจตุจักร เขตจตุจักร กรุงเทพฯ 10900

โทร. (02) 936-1840-48 โทรสาร. (02) 936-1861

