

THAI PETROLEUM & TRADING CO., LTD.

9-10th Floor, TP & T Tower 1, Soi Vibhavadee-Rangsit 19 Chatuchak, Chatuchak, Bangkok 10900, Thailand Tel. (662) 936-1840-48 Fax. (662) 936-1861 http://www.thaipet.com Email : sales@thaiper.com

STATES ULTRA MP GREASE

Product Descriptions

STATES ULTRA MP is lithium base greases, which contain rust and corrosion inhibitors. The additives also afford mild pressure protection. **STATES ULTRA MP** show excellent shear stability with little change in consistency during use or storage. Because of their buttery smooth texture, they pump well through all types of pressure systems, including centralized lubricating systems.

Application

STATES ULTRA MP is an excellent lubricant for ball and roller bearing, bushings, cams, splines, universal joints, pins, bars and slides on passenger cars, trucks, motorcycles, boat trailers and other applications on industrial off-road equipment. **STATES ULTRA MP** will also find used in industrial ball and roller bearings. The various NLGI Number Grades are available for the various applications.

Features

- Minimum change in consistency
- Saves on inventory investment because they cover a wide range of applications
- Good pump ability allows use through centralized systems
- Prevents rust and corrosion

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES STATES ULTRA MP GREASE

NLGI Grade Thickener Type Texture Color3 Lithium 12-OH Smooth YellowPenetration @ 25°C (Worked)ASTM D-217235 235Penetration @ 25°C (Unworked)ASTM D-217230 230Dropping Point, °CASTM D-2265204 400Water Washout, %Loss @79 °CASTM D-12640.55 0.55Copper Strip CorrosionASTM D-40481a 0il Separation @100 °C, %wtViscosity Kinematics @40 °C, cStASTM D-445181.4 17.66Wiscosity IndexASTM D-44517.66	Test	METHOD	TYPICAL RESULTS
\bigcirc ,	NLGI Grade Thickener Type Texture Color Penetration @ 25°C (Worked) Penetration @ 25°C (Unworked) Dropping Point, °C Water Washout, %Loss @79 °C Copper Strip Corrosion Oil Separation @100 °C, %wt Viscosity Kinematics @40 °C, cSt	ASTM D-217 ASTM D-217 ASTM D-2265 ASTM D-1264 ASTM D-4048 JIS K 2200 ASTM D-445	3 Lithium 12-OH Smooth Yellow 235 230 204 0.55 1a 2.48 181.4
	<u> </u>	ASTM D-2270	95

Rev. 04 Effective Date : October 1, 2020

Page 1/1



บริษัท น้ำมันปิโตรเลียมไทย ำำกัด

เลขที่ 1 อาคาร ที พี แอนด์ ที ชั้น 9-10 ซอยวิภาวดีรังสิต 19 แขวงจตุจักร เขตจตุจักร <mark>กรุงเทพฯ 10900</mark>

โทร. (02) 936-1840-48 โทรสาร. (02) 936-1861